

# TECHNICAL FILE

Update of the document : 04/01/2016  
ISO reference of the document : DON/LS 03.4201.A



## LEMAITRE

LEMAITRE SECURITE SAS  
17 rue Bitschhoffen  
BP 90024

F 67350 La Walck FRANCE  
Tél. : +33 (0)3 88 72 28 80  
Fax : +33 (0)3 88 07 05 37  
[www.lemaitre-securite.com](http://www.lemaitre-securite.com)  
[info@lemaitre-securite.com](mailto:info@lemaitre-securite.com)



### GOBI S3 SRC

Low shoe in water-repellent  
pull up leather

### PROTECTIONS FOR THIS MODEL



Sizes available from 35 (2) to 50 (13)  
Weight of one pair in size 42: 1500 gr.  
Norm EN ISO 20345 : 2011  
AET N° 0075/007/161/10/07/0372 –  
EXT 02/07/08

### Upper features

- Upper : water-repellent pull up leather
- Tongue : water-repellent pull up leather
- Lining : Cambrelle®
- Vamp lining : synthetic
- Backpart : synderm
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

### Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : texon
- Insock : foam and textile

### Sole features

- Name : ALPEX
- Material : rubber
- Slip resistance SRA (flat) : 0,32 / (heel) : 0,28

### Protections

- Toecap : steel
- Anti-perforation insert : stainless steel

### Basics and additional requirements of the norm EN ISO 20345

- Steel toecap
- Polycarbonate toecap
- Aluminium toecap (200 joules)
- Stainless steel composite (high tenacity fabric)
- A** A Antistatic footwear.
- Ci** Ci Cold insulation of sole complex.
- E** E Energy absorption of seat region.
- Fo** FO Resistance of the outsole to fuel oil.
- Hi** HI Heat insulation of sole complex.
- Hro** HRO Resistance of the outsole to hot contact.
- M** M Metatarsal protection.
- P** P Penetration resistance
- Wru** WRU Water penetration and water absorption resistant upper.
- Wr** WR Water resistant footwear.



Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :  
SRA (flat) ≥ 0,32  
SRA (heel) ≥ 0,28  
SRB (flat) ≥ 0,18  
SRB (heel) ≥ 0,13

### Advantages = End users benefits

- ➔ **2.0-2,2 mm thickness water-repellent pull up leather for the upper** for better resistance and durability.
- ➔ **Cambrelle®** as lining for a better comfort.
- ➔ **Designed safety shoes.**
- ➔ Very good well fitting : very flexible and comfortable even in extreme conditions.
- ➔ **Non-metallic shoe, non-magnetic, undetectable by security gates.**
- ➔ Sole : Alpex
  - Rubber, stitched sole
  - Resistant to contact heat and hydrocarbons
  - Profile with **many studs and grooves.**
  - Insulating against cold.
- ➔ Safety shoe **available up to size 50.**